



Rubberized foundation coating

CR360

The CR360 is a rubberized foundation coating that can be applied on dry or wet surfaces. It waterproofs concrete foundations, masonry and wood structures by creating a waterproofing membrane to protect the substrate. Composed with elastomer, this product has better weather resistance and greater flexibility compared to regular coatings. It forms a robust and elastic coating at the same time.



Advantages

- Enriched with rubber
- Forms a membrane on uneven surfaces
- Protects surfaces against moisture
- Easy application at all temperatures
- Applies on a wide variety of substrates

Functions

Waterproof

Building components

Foundation

Surfaces

Concrete
Masonry
Wood

Application tools

Roller
Paint brush
Spray gun

Application temperature

10°C and more preferably. The product will be thicker when the temperature decreases.

Service temperature

-40°C to 85°C

Covering rate

1,75 m²/L
70 ft²/gallon

Standard

CAN/ONGC 37-GP-6MA

Colors

Black

Density

0,85-0,95

Surface preparation

Surfaces must be clean and free of dust, dirt or other contaminants. For the waterproofing of a new foundation, first seal the gap between the footing and the wall foundation using a bead of Rubberized Plastic Cement CR320 from Condor. Use the same product to fill holes, cracks, weak spots in the foundation and the tie rod.



Application

Do not apply if rain is expected. During colder periods, keep the product in a temperate place to facilitate its application. Stir well before application. Apply the product in an even layer. Let dry completely before covering or backfilling to avoid premature product deterioration, thus allowing moisture to infiltrate. Close the container after each use.

Drying

Allow about 4h for surface drying and about 48h for complete drying. The drying time depends on the application method, the ambient temperature, the surface and the thickness applied.

Cleaning

Mineral spirits

Storage

The product may be kept in its original sealed container up to 12 months after the date of purchase by the user.

Format

3,78L / 18,9L

Restriction / Caution

Do not use on a new asphalt shingle roofing. Keep out of the reach of children. If the product is applied near a ventilation or air conditioning unit, take the necessary precautions to prevent infiltration of solvent odours toward the inside. Keep open container or freshly applied product away from open flames, sparks or other sources of heat. For outdoor use only.

Warranty

10 years limited warranty when installed and / or applied as recommended by the manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid factory (FAB factory).



2645-B, boul. Terra-Jet, Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474-6661



819 474-6681



www.condor.pro

DANGER



Flammable liquid and vapour.

May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

PRECAUTIONARY: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/ fumes/ gas/ mist/ vapours/ spray. Wash exposed and/or contaminated area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or a doctor. **IF ON SKIN:** Wash with plenty of water and soap. **IF INHALED:** Call a POISON CENTER or doctor/ physician if you feel unwell. **IF EXPOSED:** Call a POISON CENTER or doctor/ physician. Call a POISON CENTER or doctor if you fell unwell. **IN CASE OF FIRE:** Use water fog, foam, dry chemical or carbon dioxide. Do not use straight of water. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/ container by a local waste disposal company according to regional regulations.