

Ridge vent for roof OPTI-KFA96



This new, patent-pending vent is made of high-quality galvanized metal. Its advanced aesthetic and discreet design offers the same performance as a regular 4-fin vent. Whether for a regular ventilation or cathedral roof, this model allows to evacuate and exchange the air in the attic on an ongoing basis. This system reduces the accumulation of heat and moisture in the attic. Openings shaped from the vent structure eliminate the need for long-term maintenance and prevent the intrusion of insects, birds and rodents into the Interior. To ventilate a surface of 1400 sq. ft. with attic, use an already pre-packaged set comprising 2 sections of 48", 2 caps and a gasket. For a cathedral roof be sure to measure the length of the ridge. Order the number of 48" sections required to cover the ridge with the number of seals and the two caps.

Advantages

Optimizes and evenly tempers attic ventilation Facilitates the evacuation of heat and condensation Preserves the integrity of attic materials The design of the ventilator fits very well to the ridge of or shingle roofs and allows a beautiful finish The assembly and installation are very easy Aesthetic and discreet on your roof Fast manufacturing lead times Adjustable on slopes from 4/12 to 15/12

Colours

Standard colours available: brown, grey, black and charcoal. Other colours available on special order (additional fee).

Norms

CSA Certified

The National Building Code requires adequate ventilation of the roof as per the minimum standard of Section 9.19.1 or according to the ACNOR CAN3-A93-M82.


Use

Ventilation is required by the Canadian Building Code. A good ventilation means keeping the attic space near the outside temperature to avoid excessive contrasts. With the help of soffits, for example In summer, the chimney effect created by the Optimum ventilator eliminates excess heat from the attic and thus helps maintain the integrity of the asphalt shingles. In winter, you will get a drier attic. No matter what the season, Optimum Ventilators will help to optimize the comfort of your home!

Characteristics

The vent is manufactured from galvanized steel followed by a specialized baked paint finish.





PRODUCT	DIMENSIONS							STEEL GAUGE
	A	В	С	D	E	F	EVACUATION	USED
OPTI-KFA96	2 sections of 48"	9"	3"	2,36"	4,50"	1"	0,13 m² • 210 po²	24 & 26

Custom model

Custom models are available as special order. *We can manufacture any other size on request.

Warranty

The consumer must ensure that this product is appropriate for the intended use. Since the installer's skills and surface conditions are independent of the manufacturer's control, we limit our liability to the replacement of defective equipment only if proof of purchase can be provided. Free on board (FOB factory).

